Imatest Collimator Fixture

Relay lens system for simulating large test distances

Why the Imatest Collimator Fixture?

Cameras with long-focus distances can be difficult to test in a compact space. Testing your imaging system at distances up to infinity can be achieved using relay optics. The Collimator Fixture is adaptable to numerous camera systems by providing adjustable simulated test distances, interchangeable collimating lenses, and a variety of charts.

Included with the Fixture:

- ✓ Joystick and computer-control interface for automatic positioning using four motorized stages.
- ✓ Storage and recall of device positions.



Size: 1061mm length x 740mm width x 783mm height

(For ILP-G configuration, width is 1305mm)

Requirements

- ✓ Entrance pupil diameter of device under test must be less than or equal to the exit pupil size of the collimating lens.
- ✓ Camera needs to be aligned precisely with the optical axis of the collimator.



Available Collimator Lenses

Lens	Wavelength	FOV	Exit Pupil Size	Virtual Object Distance
CL736i	Visible	70°	15.0mm	400mm - Infinity
CL921e	Visible	90°	4.5mm	400mm - Infinity
CL1021i	Visible	100°	4.5mm	400mm - Infinity
CL1223i	Visible	120°	4.5mm	350mm - Infinity
CL825I	IR (850nm, 940nm)	80°	4.0mm	400mm - Infinity
CL921IR	IR (850nm, 940nm)	90°	4.5mm	400mm - Infinity



70° Medium Field of View

Collimator Lens







90° Field of View Collimator Lens for Mobile



120° Wide Field of View Collimator Lens

Light Panel	Chart Size	Illumination	
С	456mm x 327mm	Visible 100 - 1000 lux 3100K, 4100K, 5100K, 6500K	
D	634mm x 454mm		
F	931mm x 702mm	NIR	
G	1253mm x 706mm	2 ~ 20 W/m ² 850nm or 940nm	

